CUSTOMER:	SERIAL No:	ORDER No:

All dimensions in mm





FLOORLESS

ROLL IN BLAST CHILLER

CONTROLS:
WEB CONTROLLER (C/W PRINTER)

AMPS:
WMBC 175/220/350: 16Amps

SUPPLY:
208-230v / 60hz / 3ph

FINISH:

INT	441 S/S	☐
	WHITE PVC	☐
EXT	430 S/S	☐
	441 S/S	☐
	WHITE PVC	☐

CAPACITY:

WMBC175	175lbs / 90mins
WMBC220	220lbs / 90mins
WMBC350	350lbs / 90mins

MAIN EQUIPMENT:

WMBC175	2x EVAPORATOR FANS	☐
WMBC220	2x EVAPORATOR FANS	☐
WMBC350	3x EVAPORATOR FANS	☐

EVAPORATOR COIL c/w EXP VALVE
GAS R404a
ELECTRIC DEFROST

STORAGE POD EQUIPMENT:
1 FAN POD (50mm)
EVAPORATOR COIL c/w EXP VALVE
GAS R134a
ELECTRIC DEFROST
ELEC VAP TRAY
COND UNIT 0.5 HP

DRAIN FACILITY REQUIRED

CONDENSING UNIT:
BTU REQUIREMENTS AT 32°C / 90°F AMBIENT

MODEL	BTU's / HOUR
WMBC175	29340 " 5°C EVAP
WMBC220	34250 " 5°C EVAP
WMBC350	59080 " 5°C EVAP



Williams Refrigeration Bryggen Road North Lynn Industrial Estate kings lynn, Norfolk, PE30 2HZ	This drawing and all copies produced are the property of Williams Refrigeration and must not be copied or distributed by any third party without obtaining authorisation.	DRAWING TITLE: WMBC 175/220/350 FE c/w POD ROLL-IN BLAST CHILLER (BEV-AIR SPEC)	DRAWN BY: JJA CHECKED BY:	DATE: 14/02/14 DATE:	SCALE: 1:25 DRAWING NUMBER: E:/Spec-Drg/Bev-Air WMBC/WMBC 175-220-350 FE Pod	ISSUE: 001